

MAULDIN

1550-C

- **FREEDOM-FOUR** screed with patented extension matching system
- Four auger material feed system with extending extension augers feeds to 13' with ease
- Heated screed extensions
- Fully enclosed & sound attenuated engine compartment
- 60 HP John Deere diesel engine
- Two-speed polyurethane crawler track drive system
- Night operating light kit
- Fully enclosed engine with no muffler exhaust system



1550-C SUPER PAVER

DIMENSIONS		OPERATION	
Length	10'-4"	Steering	Hydrostatic – Skid
Width, Hopper In	8'-6"	Steer	
Width, Hopper Out	10"	Paving Speed (2 Speed)	0 – 140 FPM, 43 MPM
Height	5'-4"	Travel Speed	0 – 290 FPM, 89 MPM
Truck Clearance	23	HOPPER	
WEIGHT		Capacity	6.5 tons (US)
Crawler Track	12,500 lbs	Double Conveyor, Width	60"
CRAWLER TRACK SUSPENSION		FREEDOM™ FOUR SCREED	5,900 kg
Length	71'	8' - 13' Vibratory Screed	
Tensioner	Automatic/Hydraulic	9" Extending Augers	
Drive	Planetary Sprocket	Extending Walkboard	
Track Rollers (Bottom)	(8) Oil Metal Faced	Patented Automatic Adjustment for Seamless Match with Main Screed	
Idle Rollers (Top)	(2) Oil Metal Faced	Propane torch heating for main screed with dedicated extension torches	
ENGINE		Replacement Extension Wear Plate	
Manufacturer	John Deere	Chrome Guide Rods	
Fuel Type	Diesel	High-Load, Self Lubricating Bearings for Slide Mechanism	
Horsepower (SAE J1349)	60	OPTIONAL EQUIPMENT	
Kilowatts	45	Seat	
Type & Cooling	4 Cylinder Water	M-Brella Sunshade	
Electrical System	12 Volt	Truck Hitch	
CAPACITIES		MODEL 1500-C ECONOMY PACKAGE	
Fuel Tank	13 gal	HP 49	Travel Speed 0 – 170 FPM, 52 MPM
Hydraulic Tank	15.5 gal	Contacting Feed Switches	Enclosed Engine – No Insulation
TRANSMISSION			Steel Tracks
Manufacturer	Rexroth		No lights, horn, gauges
	Tandem Hydrostatic		

01.15.07
Specifications subject to change without notice.



Sold and Serviced By:

Statesville, NC
(800) 984-8080 www.apellic.com