

550E

RUBBER TIRE OR CRAWLER TRACK

- Gear-driven steering system provides precise control and a true neutral position.
- Superior o-ring face seal hydraulic system.
- Featuring leak-proof hoses from Parker Hose.
- True crawler tracks offer no-slip traction at all times.
- Tire paver has best tractive effort in its class.
- Wide, foam-filled, pneumatic tires provide superior flotation (without worry of going flat).
- Extending augers feed extensions without use of shovels.



550-E GRAVITY-FEED ASPHALT PAVER

DIMENSIONS	CRAWLER TRACK	RUBBER TIRE	OPERATION				
Length	98"	249 cm	92"	234 cm	Paving Speed	0 – 140 FPM	43 MPM
Width, Hopper Open	118"	299 cm	118"	299 cm	Hopper Lift	Two Hydraulic Cylinders	
Width, Hopper Closed					Material Flow Gates	Two, 4" Hydraulic Control	
8' Screed	101"	257 cm	101"	257 cm	Screed Lift	Hydraulic Cylinder	
CRAWLER TRACK SUSPENSION				CAPACITIES			
Track-to-Track Width	95"	241 cm	95"	241 cm	Gravity Feed Hopper	6 tons (US)	5,443 kg
Height	65"	165 cm	65"	165 cm	Fuel Tank	13 gal	49 lit
Truck Clearance	20"	51 cm	21"	53 cm	Hydraulic Oil Tank	17.5 gal	66 lit
WEIGHT				Washdown System			
23 HP 17 KW	8,300 lbs	3,765 kg	7,800 lbs	3,538 kg	FULLY FLOATING SCREED		
*28 HP 21 KW	8,300 lbs	3,765 kg	7,800 lbs	3,538 kg	Heating System	Propane with Lighting Wand	
*Higher Power Rating Recommended for Altitude Paving. See Your Dealer for a Review of Your Application.							
RUBBER TIRE SUSPENSION (ALL WHEEL DRIVE)				GOLD KEY OPTIONS PACKAGE			
Length	51"		130 cm	8' – 13' Vibrating Screed with 9" Augers			
Ground Coverage	1,224 sq in	7	,897 cm ²	Automatic Auger Feed			
Bolt-On Rubber Track Pads		Optional		Horn			
Bolt-On Polyurethane Track Pads		Optional		Extendable Walk Board			
QUANTITY				Adjustable End Gate			
Quantity	6			Dual Washdown Sprayers			
Foam-Filled Tire Dimension	8" x 20.5", 10 Ply			Electronic Engine Hour Meter			

01.15.07
Specifications subject to change without notice.



Sold and Serviced By:



Statesville, NC
(800) 984-8080 www.apellic.com